

## **GHS SAFETY DATA SHEET**

Prepared to U.S. OSHA Standards in compliance with the GHS system (29 CFR 1910.1200(g), rev. 2012

Section 1	Identification	Beet Molasses  Manufacturer's Name    American Crystal Sugar Co.    101 North 3 rd Street    Moorhead, MN 56560  Emergency Telephone Number:    (218) 236-4400  Telephone Number for Information    (218) 236-4324		Livestock and poultry feed	
Section 2	Hazard(s) Identification	No Hazardous Components  Beet molasses is non-hazardous under normal conditions of use, storage, and handling.  Molasses that has dried supports combustion only poorly and is not by itself a hazard unless it is involved as a secondary fuel in an existing fire.		Very rarely, hot sugar products and their syrups have been known to exhibit "runaway behavior"; explosions have been known to occur under a combination of specific conditions. (Please see: §VII – Handling and Storage, "Conditions to Avoid."	
Section 3	Composition / Information on Ingredients	Beet molasses is a concentrated mit (composition may vary greatly) from from which 85% of the sucrose has Sugar (Sucrose), CAS 57-50-1  Ash  Water, CAS 7732-18-5  Miscellaneous Organics, including Amino Acids	15 – 2	sugar beet root (Beta vulgaris)	

Section	First Aid Measures	SKIN: Radness and/or blistering of skin. If	ALLERGIC REACTIONS:	
4	THE AIGHTES	SKIN: Redness and/or blistering of skin. If hot material gets on skin, flush affected area with cool water; seek medical attention in case of thermal burns.  EYES (irritation of eyes from dissolved salts): immediately flush with running water, holding eyelids open. Get medical help if symptoms persist.  Non-toxic, but non-palatable; contains bitter-tasting salts and organics.	Because sugars are prime feedstock for molds and yeasts, it is conceivable spore-formers could grow under conditions required for their growth. In the event of exposure to these spores, susceptible individuals may require specialized medical attention.	
Section 5 Section 5	Fire-Fighting Measures	If material has solidified, use water or other approved media.  Thermal decomposition or burning will produce carbon dioxide, carbon monoxide.  Normal fire dept SOP for precautions and PPE.	Avoid extreme heat in closed containers and pipes which may lead to uncontrollable spontaneous combustion (see §VII – Precautions for Safe Handling and Use, "Other Precautions").	
Section 6	Accidental Release Measures	Since material is non-toxic and biodegradable, it may be washed down with water. Material may be hot and is slippery. Clean-up personnel should wear proper protective equipment: goggles or face shield, thermal insulating gloves and non-slip boots.	Spilled material may be pumped into a closed tank for recovery or disposal. Whatever cannot be saved for recovery may be discarded as permitted by applicable regulations.	
Section 7	Handling and Storage	especially molasses, have been known to e under the <i>combined conditions</i> of (1) prese enclosed space including piping where prese temperatures above 110 °C; (4) extended per than 5 hours); (5) lowered pH; (6) increases adequate thermal transfer.  Though extremely rare, explosions have been these <i>combined conditions</i> . See Platje, T. e. 'Runaway Behavior' of Technical Sucrose Stat, 231 – 238.  Therefore: <i>Avoid using steam to loosen in the combined conditions</i> .	bugh extremely rare, explosions have been known to occur under se <u>combined conditions</u> . See Platje, T. et al. (2006): "Study of the naway Behavior' of Technical Sucrose Solutions." <i>Zuckerindustrie</i> 1., 231 – 238.  Exercise Prefere: <b>Avoid using steam to loosen material in plugged piping</b> after those conditions listed above without proper pressure relief	

Section 8	Exposure Controls / Personal Protection	None normally required. In case of hot material, wear goggles, and thermal-protective gloves and boots.  Sensitive skin may be irritated by continued contact with product; transferring product using high temperatures may cause burns.		In cases of water being used to flush spilled material, floors and steps may become sticky. Use proper footwear when negotiating floors and steps.	
Section	Physical and Chemical	Melting Point	N/A	Flash Point	N/A
9	Properties	<b>Boiling Point</b>	N/A	Flammable Limits	N/A
		Specific Gravity (H2O = 1)	1.348 – 1.385	LEL	N/A
		Evaporation Rate (Butyl Acetate = 1)	N/A	UEL	N/A
		Vapor Pressure (mm Hg)	N/A	Appearance a	
		Vapor Density (AIR = 1)	N/A		black-colored
		Solubility in Water:	infinitely soluble	viscous mass; mildly caramel to bitter amine odor.	
Section 10	Stability and Reactivity	Stable under ordinary conditions of use and storage. Hazardous polymerization will NOT occur.  Avoid temperatures above 120 °F, pH less than 7, and incompatibles.		Avoid strong oxidizers (e.g. nitric acid or sulfuric acid).  Thermal decomposition or burning will produce carbon dioxide, carbon monoxide.	
Section 11	Toxicological Information	Non-toxic		Product contains no ingredients currently classified as carcinogenic by NTP, IARC, or OSHA.	
Section 12	Ecological Information (non-manditory)	Non-toxic and biodegradable.			
Section 13	Disposal Considerations (non-manditory)	Whatever cannot be saved for recovery may be discarded as permitted by applicable regulations.			
Section 14	Transport Information (non-manditory)	Not applicable			
Section 15	Regulatory Information (non-manditory)	Not ordinarily regulated. (Note some countries do have import quotas which restrict total amount of sugar entering their borders.)			

Section	Other Information	Avoid vaine storm to locace mentorial in always defining under these
16		Avoid using steam to loosen material in plugged piping under those conditions listed above without proper pressure relief devices due to
		possible exothermic "runaway behavior" referenced earlier in this
		document:
		§VII – Handling and Storage, "Conditions to Avoid."
		Slippery! Avoid excessively high temperatures. However, cold
		conditions will increase viscosity. If product temperature is kept
		between 80 – 120 °F (27 – 50 °C), flowability will be maintained and
		decomposition prevented.